

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 2 of 12

### AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### LISTING OF CLAIMS:

Claim 1 (Original): A method of cleaning a CVD vacuum vessel which has an electrically conductive partition plate which divides an interior of the vacuum vessel into a plasma generating space and a film-deposition processing space, and in the electrically conductive partition plate there is a plurality of through-holes connecting the plasma generating space to the film-deposition processing space, the method comprising the steps of:

feeding a cleaning gas into the plasma-generating space;

generating active seeds by applying high-frequency electric power to electrodes arranged in the plasma-generating space;

feeding the generated active species into the film-deposition processing space through the plurality of through-holes in the electrically conductive partition plate;

heating said electrically conductive partition plate; and

cleaning the film-deposition processing space by the active seeds which have been fed into this film-deposition processing space.

Claim 2 (Original): The method of claim 1, further comprising the step of maintaining the electrically conductive partition plate at ground potential.

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 3 of 12

Claim 3 (Canceled)

Claim 4 (Original): The method of claim 1, wherein the cleaning gas is one or more types of fluoride gas.

Claim 5 (Original): The method of claim 4, wherein the fluoride gases are  $\text{NF}_3$ ,  $\text{F}_2$ ,  $\text{SF}_6$ ,  $\text{CF}_4$ ,  $\text{C}_2\text{F}_6$  and  $\text{C}_3\text{F}_8$ .

Claim 6 (Original): The method of claim 1, further comprising the step of adding oxygen gas to the cleaning gas.

Claim 7 (Original): The method of claim 6, wherein an amount of oxygen gas added is such that the concentration is 60% or less.

Claim 8 (Withdrawn): The method of claim 1, wherein the cleaning gas is  $\text{O}_2$ .

Claim 9 (Original): The method of claim 1, further comprising the step of adding any of He, Ne, Ar, Kr and Xe to the cleaning gas.

Claim 10 (Currently Amended): The method of claim 1, wherein the heating of said electrically conductive partition plate is carried out within a temperature range which

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 4 of 12

inhibits the adsorption of fluorine onto an inner circumferential face of the through-holes and the surface of the partition plate:

Claim 11 (Original): The method of claim 10, wherein the cleaning gas is carbon fluoride gas or nitrogen fluoride and the electrically conductive partition plate is heated to 200°C or more.

Claim 12 (Original): The method of claim 10, wherein the cleaning gas is sulfur fluoride gas and the electrically conductive partition plate is heated to 100°C or more.

Claim 13 (Currently Amended): A method of cleaning a CVD system, the CVD system ~~having in which active species are produced by generating plasma inside a vacuum vessel and film is deposited on a substrate accommodated in the vacuum vessel by the active species and material in gas form; wherein said CVD system is configured in such a way that, by providing said vacuum vessel with an electrically conductive partition plate; wherein the interior of said vacuum vessel is divided into a plasma generating space and a film deposition processing space two chambers by said an electrically conductive partition plate, said plate comprising a plurality of through-holes and in the interior of one of said two chambers into which the interior of the vacuum vessel is divided, a plasma generating space in which high frequency electrode is arranged is formed, and in the interior of the other chamber a film deposition processing space in which there is arranged a substrate holding mechanism on which said substrate is mounted is formed, said CVD system is~~

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 5 of 12

~~configured in such a way that in said electrically conductive partition plate there is a plurality of through-holes made to pass through said plasma-generating space and said film-deposition processing space, the plurality of through-holes are formed in such a way that where the velocity of gas flow inside said through-holes is  $u$ , the effective length of the through-holes is  $L$  and the coefficient of mutual gas diffusion is  $D$ , the following condition  $uL/D \geq 1$  is fulfilled, and an interior space is formed therein which is divided off from said plasma-forming space and which communicates with said film-deposition processing space via a plurality of diffusion holes, and said material in gas form is supplied to the interior space of said electrically conductive partition plate from the outside and fed into said film-deposition processing space through said plurality of diffusion holes, and said CVD system introduces into said film-deposition processing space, through the plurality of through-holes formed in said partition plate, said active species which are generated in said plasma-generating space by applying high-frequency electric power to said high-frequency electrodes and thus producing a plasma electric discharge in said plasma-generating space, the cleaning method comprising the steps of:~~

- ~~maintaining the electrically conductive partition plate at ground potential;~~
- ~~feeding a cleaning gas into the plasma-generating space;~~
- ~~generating active seeds by applying high-frequency electric power to electrodes arranged in the plasma-generating space;~~
- ~~feeding the generated active seeds into the film-deposition processing space through the plurality of through-holes in the electrically conductive partition plate;~~
- ~~heating said electrically conductive partition plate; and~~

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 6 of 12

cleaning the film-deposition processing space by the active species which are fed into this film-deposition processing space.

Claim 14 (Canceled)

Claim 15 (Original): The method of claim 13, wherein the cleaning gas is one or more types of fluoride gas.

Claim 16 (Original): The method of claim 15, wherein the fluoride gases are  $\text{NF}_3$ ,  $\text{F}_2$ ,  $\text{SF}_6$ ,  $\text{CF}_4$ ,  $\text{C}_2\text{F}_6$  and  $\text{C}_3\text{F}_8$ .

Claim 17 (Original): The method of claim 13, further comprising the step of adding oxygen gas to the cleaning gas.

Claim 18 (Original): The method of claim 17, wherein an amount of oxygen gas added is such that the concentration is 60% or less.

Claim 19 (Withdrawn): The method of claim 13, wherein the cleaning gas is  $\text{O}_2$ .

Claim 20 (Original): The method of claim 13, further comprising the step of adding any of He, Ne, Ar, Kr and Xe to the cleaning gas.

Attorney's Docket No. 001425-117  
Application No. 10/043,190  
Page 7 of 12

Claim 21 (Original): The method of claim 13, wherein the heating of said electrically conductive partition plate is carried out within a temperature range which inhibits the adsorption of fluorine onto the inner circumferential face of said through-holes and the surface of the partition plate.

Claim 22 (Original): The method of claim 21, wherein the cleaning gas is carbon fluoride gas or nitrogen fluoride and the electrically conductive partition plate is heated to 200°C or more.

Claim 23 (New): A CVD apparatus comprising:

- a vacuum vessel separated into two chambers;
- the first one of the two chambers containing a radio-frequency electrode;
- the second one of the two chamber containing a substrate support mechanism for mounting a substrate;

wherein said vacuum vessel is separated by an electrically conductive partitioning section, said partitioning section comprising:

- a plurality of through-holes to allow communication between the first chamber and the second chamber;
- an interior space for receiving a reactive gas, the interior space separated from the first chamber and communicating with the second chamber through a plurality of diffusion holes; and

- a heater for heating the electrically conductive partition section.

Attorney's Docket No. 001425-117Application No. 10/043,190

Page 8 of 12

Claim 24 (New): The apparatus of claim 23, further comprising:

an electrically conductive spiral shield; and

---

wherein the partitioning section is mounted to the vacuum vessel by means of a mounting screw such that electrical contact between the partitioning section and the vacuum vessel is achieved through said spiral shield.